## 2021 FireFly ESV Specifications

MOTOR		FEATURES	
63 HP (47KW) AC Induction	STD	Integrated passenger safety cell	STD
		Textured ABS, UV-protected body panels	STD
BATTERY PACK		Extra-low step-in height of less than 10 in (25 cm)	STD
102 V (nominal) 20.5kWh Lithium Iron Phosphate	STD	> Maximizes operator comfort and minimizes fatigue	
SPEED & RANGE		rabalar seed in one arra rear barripers	STD
Electronically Governed - Maximum 55 mph	STD	High-visibility, tinted, haze/scratch/impact-resistant polycarbonate windows	STD
100+ Miles per charge (under normal operation)	STD		STD
Too Imag per crisings (under riormal operation)		3-Speed intermittent windshield wiper system with washer	STD
TRANSMISSION			STD
Computer Controlled Integrated Drive System <sup>™</sup> (IDS)	STD	3-Point seat belt system	STD
ELECTRICAL SYSTEM			STD
		Dome light and backlit controls for nighttime use Easily removable and replaceable heavy-duty floor mat	STD STD
SAE J1772 3kW (Level 2) charger	STD		STD
> Less than 6hr charge time under normal use Halogen headlights & LED stop, tail and turn lamps	STD	openings, and pockets	5.5
"Auto-Park" Parking Brake feature	STD	Pre-wired and integrated speaker mounts for optional	STD
Automatic Hill Assist feature - minimizes rollback on steep grades	STD	AM/FM/MP3 player	
Electronic Controlled Drive/Variable-rate electronic drive	STD		STD
system optimizes speed and range		accessories Up to four additional 12V DC accessory ports	STD
Electronic Stability Control System (ESC) with 3-axis accelerometer	STD	NAME OF THE PARTY	STD
and Integrated vehicle ride sensors		ALPR, Light Bars, Warning Lights, etc.	5.5
> Automatically adjusts speed & ride for maximum stability		Integrated rails in bed floor to secure cargo and mount for op-	STD
CLIMATE CONTROL		tional accessories	
Heating – Electronic, 3 KW heater/defroster	STD	Deluxe bed with tri-fold, locking, and stowable bed cover Dual Mode Display	OPT
2.3KW diesel/biodiesel supplemental heater	OPT	Sauge pod display of operational information and on-board	STD
4000 BTU air conditioning system	OPT	parameters	
		> Provides estimated miles remaining, battery charge level,	
SUSPENSION & STEERING	STD	J. ,	
DuraSteer <sup>™</sup> front suspension	טונ	av TCCONNICCT Valida Managamant Costana	
> Proprietary load distributing front end with anti-dive control and coil-over shocks		evTSCONNECT Vehicle Management System	
> Outside frame mounted heavy-duty rear leaf springs with coil-			STD
over shocks		operations of the vehicle > (eDAS) Digital Acquisition System <sup>™</sup> , performance data log-	STD
		ging, remote data access, diagnostics, and alerts	טונ
BRAKING		Optional Fleet Management System	OPT
Tuned dual-circuit master cylinder and disk brakes	STD		
Electric Parking Brake (EPB)	STD	TIDEC	
BODY/FRAME/COLORS		TIRES	CTD
Welded tubular steel frame with integrated safety cell	STD	175/65-14 all-season radials *snow and ice rated where appropriate	STD STD
Textured white ABS outer skin (color molded in) w/UV protection	STD	show and ice rated where appropriate	
		WEIGHT CAPACITY	
CEATC		GVWR - 3500 pounds	
SEATS			
Single Passenger Bucket seating	STD	Rated Capacity – 1100 pounds (incl. driver)	
Single Passenger Bucket seating Tandem seating available - left or right hand drive	STD OPT		
Single Passenger Bucket seating		EXTERIOR DIMENSIONS	
Single Passenger Bucket seating Tandem seating available - left or right hand drive Seat heaters DOORS		EXTERIOR DIMENSIONS  Overall cab height 69 in (175 cm)	
Single Passenger Bucket seating Tandem seating available - left or right hand drive Seat heaters		EXTERIOR DIMENSIONS  Overall cab height 69 in (175 cm)  Overall length 152 in (386 cm)	
Single Passenger Bucket seating Tandem seating available - left or right hand drive Seat heaters DOORS	OPT	EXTERIOR DIMENSIONS  Overall cab height 69 in (175 cm)	
Single Passenger Bucket seating Tandem seating available - left or right hand drive Seat heaters  DOORS LinearGlyde™ door system maintains narrow vehicle profile  > Self-cleaning large diameter cushioned rollers  > Powder coated steel tubes and four point, load-balanced,	OPT	EXTERIOR DIMENSIONS  Overall cab height 69 in (175 cm)  Overall length 152 in (386 cm)  Overall width 54 in (137 cm)	
Single Passenger Bucket seating Tandem seating available - left or right hand drive Seat heaters  DOORS LinearGlyde™ door system maintains narrow vehicle profile  > Self-cleaning large diameter cushioned rollers  > Powder coated steel tubes and four point, load-balanced, crosslinked mechanical design for maximum stability	STD	EXTERIOR DIMENSIONS  Overall cab height 69 in (175 cm) Overall length 152 in (386 cm) Overall width 54 in (137 cm) Ground clearance 6 in (15 cm)	
Single Passenger Bucket seating Tandem seating available - left or right hand drive Seat heaters  DOORS LinearGlyde™ door system maintains narrow vehicle profile  > Self-cleaning large diameter cushioned rollers  > Powder coated steel tubes and four point, load-balanced,	OPT	EXTERIOR DIMENSIONS  Overall cab height 69 in (175 cm) Overall length 152 in (386 cm) Overall width 54 in (137 cm) Ground clearance 6 in (15 cm) Outside turning radius 22 in (310 cm)	





1309 Beacon Street, Suite 300 Brookline, MA 02446 USA Tel: (202) FIREFLY Tel: (202) 347-3359 www.evTS.com